CLASSIFICATION CONFIDENTIAL

CENTRAL INTELLIGENCE AGENCY

INFORMATION FROM FOREIGN DOCUMENTS OR RADIO BROADCASTS REPORT

CD NO.

COUNTRY USSR

SUBJECT

Economic; Technological - Machine tools

DATE OF

INFORMATION 1952-1953

HOW

PUBLISHED Monthly periodical

DATE DIST. 30 Apr 1954

WHERE

PUBLISHED Moscow

NO. OF PAGES 2

PUBLISHED Aug 1952, Jun 1953

SUPPLEMENT TO

LANGUAGE Russian

REPORT NO.

THE UNITED STATES. BITHIN THE MEANING OF TITLE 18, SECTIONS 79. AND 784, OF THE U.S. CODE, AS AMENDED. 175 TRANSMISSION OR REVE LATION OF 1TS CONTENTS TO OR RECEIPT BY AN UNAUTHORIZED PERSON ? THE REPRODUCTION OF THIS FORM IS PROMISETED

THIS IS UNEVALUATED INFORMATION

SOURCE

Podshipnik, No 8, 1952; No 6, 1953

USSR MACHINE TOOLS FOR MACHINING BEARING RACES

50X1-HUM

50X1-HUM

MODEL NUMBERS OF MACHINE TOOLS USED IN BEARING INDUSTRY -- Moscow, Podshipnik,

The following machine-tool models are used at bearing plants for machining the races of bearing No 203, 207, and 409. [Unless indicated, the letters in the model numbers have been transliterated from the Cyrillic alphabet]

Model 1261-M six-spindle automatic

Model VH-48 four-spindle semiautomatic [VH given in Roman alphabet]

Model 1262-M four-spindle automatic

Model 16-A surface-grinding machine

Model 3772-E surface-grinding machine

Model 3756 surface-grinding machine

Model SB-35 six-spindle automatic [SB given in Roman alphabet]

Model RP6/28 six-spindle automatic [RP given in Roman alphabet]

Model 371-L surface grinding machine

Model N5R [or H5P] four-spindle semiautomatic [Letters could be either Cyrillic or Roman]

CLASSIFICATION STATE NSRB DISTRIBUTION AIR

50X1-HUM

CONFIDENTIAL

50X1-HUM

Model MT-30 semiautomatic

Model 1261-P six-spindle semiautomatic

Model FRS-114 single-spindle semiautomatic

MR-5 single-spindle semiautomatic

TBSh-3 centerless-grinding machine

MODEL MR-5 SEMIAUTOMATIC LATHE -- Moscow, Podshipnik, Aug 52

Model MR-5 semiautomatic lathes produced in 1949-1950 by the Moscow Machine-Tool-Building Plant imeni Ordzhonikidze nave a main power drive of 17 kilowatts and are equipped with longitudinal, boring, and cross slides. The spindle speed is 52-400 rpm; longitudinal and boring slide feeds, up to 1.65 millimeters per revolution; and rapid slide feed, 4.5 meters per minute. The cutting tools conform to the First State Bearing Plant norm. All tools have T5KlO hard-alloy tips.

The semiautomatics are used for machining outer races for taper rolling bearings.



50X1-HUM

- 2 -

CONFIDENTIAL